


## 7/16 Attenuators - 50 OHM

AT1102		7/16 - DC To 7.5 GHz - 5 WATT		
Part #	Attenuation	1-24	25-49	Specifications

AT1102-1	1 dB	\$ 129.77	\$ 120.69
	2 dB	129.77	120.69
	3 dB	129.77	120.69
AT1102-6	6 dB	\$ 129.77	\$ 120.69
	10 dB	129.77	120.69
	20 dB	129.77	120.69
AT1102-30	30 dB	\$ 129.77	\$ 120.69
	40 dB	139.77	129.99



Accuracy: Minimum + .4 dB  
Maximum + 1.5 dB  
VSWR: 1.25:1 MAX

AT1103		7/16 - DC To 7.5 GHz - 10 WATT		
Part #	Attenuation	1-24	25-49	Specifications


AT1103-1	1 dB	\$ 194.77	\$ 181.14
	2 dB	194.77	181.14
	3 dB	194.77	181.14
AT1103-6	6 dB	\$ 194.77	\$ 181.14
	10 dB	194.77	181.14
	20 dB	194.77	181.14
AT1103-30	30 dB	\$ 194.77	\$ 181.14
	40 dB	219.77	204.39



Accuracy: Minimum + .6 dB  
Maximum + 1 dB  
VSWR: 1.30:1 MAX

AT1104		7/16 - DC To 7.5 GHz - 25 WATT		
Part #	Attenuation	1-24	25-49	Specifications


AT1104-1	1 dB	\$ 379.77	\$ 353.19
	2 dB	379.77	353.19
	3 dB	379.77	353.19
AT1104-6	6 dB	\$ 379.77	\$ 353.19
	10 dB	379.77	353.19
	20 dB	379.77	353.19
AT1104-30	30 dB	\$ 379.77	\$ 353.19
	40 dB	379.77	353.19



Accuracy: Minimum + .4 dB  
Maximum + 1.5 dB  
VSWR: 1.35:1 MAX

AT1105		7/16 - DC To 7.5 GHz - 50 WATT		
Part #	Attenuation	1-24	25-49	Specifications


AT1105-6	6 dB	\$ 379.77	\$ 353.19
	10 dB	399.77	371.79
	20 dB	399.77	371.79
AT1105-30	30 dB	\$ 399.77	\$ 371.79
	40 dB	399.77	371.79



Accuracy: Minimum + .85 dB  
Maximum + 2.5 dB  
VSWR: 1.40:1 MAX

AT1106		7/16 - DC To 1.5 GHz - 100 WATT		
Part #	Attenuation	1-24	25-49	Specifications

AT1106-6	6 dB	\$ 439.77	\$ 408.99
	10 dB	439.77	408.99
	20 dB	439.77	408.99
AT1106-30	30 dB	\$ 439.77	\$ 408.99
	40 dB	449.77	418.29




Accuracy: Minimum + .5 dB  
Maximum + .75 dB  
VSWR: 1.15:1 MAX

## 7mm Attenuators - 50 OHM

AT1107		7mm - DC To 18 GHz - 2 WATT		
Part #	Attenuation	1-24	25-49	Specifications

AT1107-1	1 dB	\$ 231.77	\$ 215.55
	2 dB	231.77	215.55
	3 dB	231.77	215.55
AT1107-6	6 dB	\$ 231.77	\$ 215.55
	10 dB	231.77	215.55
	20 dB	231.77	215.55
AT1107-30	30 dB	\$ 231.77	\$ 215.55




Accuracy: Minimum + .3 dB  
Maximum + .5 dB  
VSWR: 1.2:1 MAX

## BETWEEN Series - Attenuators

### 50 OHM DC To 2 GHz - 0.5 WATT

ATB505		N MALE To BNC MALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications


ATB505-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB506		N FEMALE To BNC MALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications


ATB506-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB507		N MALE To BNC FEMALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications

ATB507-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB508		N FEMALE To BNC FEMALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications


ATB508-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB521		SMA MALE To BNC MALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications


ATB521-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB522		SMA FEMALE To BNC MALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications


ATB522-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB523		SMA MALE To BNC FEMALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications


ATB523-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX

ATB524		SMA FEMALE To BNC FEMALE - 0.5 WATT		
Part #	Attenuation	1-24	25-49	Specifications

ATB524-3	3 dB	\$ 59.77	\$ 55.59
	6 dB	59.77	55.59
	10 dB	59.77	55.59



Accuracy: +.3dB VSWR: 1.25:1 MAX